

# Eco Solvent Printer

3.2m i3200 Printhead

3.2米 爱普生 i3200 户内外写真机

1/2/3 Printheads

1/2/3 头可选

Up To 2400dpi

高达2400dpi

4 Color

4 色写真

Variable Dot

可变墨滴

3-Stage Heater

三段加热



## ● Features 特点




### Epson PrecisionCore Printheads

Equipped with Epson i3200-E printhead, powered by Epson PrecisionCore technology. Born for fast speed and long-term running.




### Well Designed Feeding System

Two sets media feeding system are standard equipped. Enable to install both 3.2m heavy banner and 2 rolls small size paper.




### Anti-collision Function

Anti-collision system is equipped to protect the printhead and carriage all the time.



### Branded parts

Greatly increased the lifetime and stability of the machine. For example, Hiwin guide rail, German Igus drag chain, Italian Megadyne belt.



### Variable Dot Print Technology

Permitting the printer to provide smooth gradations, exceptional solid colors and optimum image quality in all print modes.

- ★ New look has heavier, larger structure, and wider printing platform
- ★ Big Functional Control Panel. Adopts the latest program Intelligent Error Auto-Detection boards, it can guide user to find solution very quickly
- ★ IGUS Drag Chain from Germany. A guarantee of quality, takes the printer stability to a new level. Effectively protect ink tube and cables
- ★ LED lamp strip is equipped, users could check out the print result more easily
- ★ Optional infrared heater for drying prints quickly



## ● Specification 参数

Model No.		型号	SJ-1260S	SJ-1260i
Printhead		喷头	2 × Epson i3200	1 × Epson i3200
Resolution		精度	2400dpi max	
Ink Color		色彩	C M Y K	
Media 耗材	Size	尺寸	3.2 meter	
	Types	种类	Flex Banner , Vinyl, One Way Vision, Banner Cloth, Window Film, Mesh Etc. 灯箱布, 车贴, 单透贴, 条幅布, 玻璃贴膜, 网格布等	
Speed 速度	Draft	标准	46 sqm/h	28 sqm/h
	Production	精细	34 sqm/h	21 sqm/h
	Quality	照片	26 sqm/h	16 sqm/h
Ink Type		墨水	Eco Solvent Ink	
Ink Droplet		墨滴	1.5-21pl variable	
Cleaning		清洗	Automatic Cleaning, Anti-Clogging Flash Function & Capping System 自动清洗、闪喷、封喷头	
Feed & take up		收放布	Automatic Media Feeding (Standard) & Take up System (Optional)	
Environment		环境	Temperature: 20-28°C, Humidity: 40%-60%	
Rip Software		软件	Maintop (Standard)/ FlexiPRINT (Optional)	
Interface		接口	USB 3.0	
Power		电源	Machine 50/60HZ, 110 / 220V, 1500W	
Size & Weight	Machine	机器	L4360 x W780 x H1500 mm / 480 KG	
	Packing	包装	L4610 x W1000 x H740 mm / 640 KG	

Specifications are subject to change without notice. 以上参数可能随机器版本改变, 请以厂家最新数据为准。