

Epson i1600/i3200 Printheads

爱普生 i1600/i3200喷头

Variable Dot

可变墨滴

Negative Pressure System

负压系统

Pre-treating Liquid Optional

处理液可选

EPSON PRINTHEAD SERIES UV FLATBED PRINTER

250×130cm




● Features 特点



Equipped with Epson i1600/i3200 print-head, powered by Epson PrecisionCore technology. Born for fast speed and long-term running.

配备爱普生i1600/i3200喷头。



Double built-in high-power independent vacuum pump. Guarantee the powerful suction.

内置独立双高功率抽风机，确保吸力强劲。




Two advanced separate negative pressure systems. Simply and effectively ensure the continuous ink flow, and easy maintenance for multi-heads equipment.

配置高级的负压系统。稳定供墨，简化多头设备维护。



Automatic media height detecting system is equipped, provide great help for setting the proper print height.

标配自动测高功能。



Anti-collision system is equipped to protect the printhead and carriage all the time.

贴心防撞系统设计，保护喷头及机架。

- ★ The high precision machine frame ensures perfect print resolution.
- ★ X axis' s gear fixation components are processed with one-time molding technology.
- ★ X axis is equipped with dual guide rail which ensures smooth movement of carriage.
- ★ Y axis is using screw drive transmission mode.



● Specification 参数

Model No.		型号	FB-2513S (Pro)	FB-2513D (Pro)
Printhead		喷头	Epson i3200-U	Epson i1600-U
Number of Printheads		数量	2/ 3/ 4 pcs optional	
Resolution		精度	Max 2400 dpi	
Media 耗材	Thickness	厚度	Max 12 cm	
	Size	尺寸	2500 × 1300 mm	
	Types	种类	Glass, Acrylic, Ceramic, Metal, Paper, Wood, Leather, PVC , PP, PE, PTFE Etc.	
Speed 速度	Draft	草图	50 sqm/h (CMYK, 4 Heads)	45 sqm/h (CMYK, 4 Heads)
	Production	标准	32 sqm/h (CMYK, 4 Heads)	28 sqm/h (CMYK, 4 Heads)
	Quality	精细	23 sqm/h (CMYK, 4 Heads)	20 sqm/h (CMYK, 4 Heads)
Ink 墨水	Type	墨水	UV Ink	
	Color	颜色	CMYK/ CMYK + W/ CMYK + W + V/ CMYK + W + V + Pre-treating Liquid	
	Capacity	墨瓶	500 ml	
	Dry System	干燥	UV-LED Light System	
Negative Pressure System			Standard	Optional
PC Operation System		系统	Windows 7/XP/10	
Environment		环境	Temperature: 20-28°C, Humidity: 40%-60%	
Rip Software		软件	Maintop (Standard) / FlexiPRINT (Optional)	
Image Format		图片格式	TIFF, JPEG, EPS, PDF...	
Power		电源	Max 3.6KW, AC 50/60Hz, 220V(±10%)>12A	
Size 尺寸	Machine	机器	L4200 × W2180 × H1590 mm	
	Packing	包装	L4300 × W2280 × H1790 mm	
Weight 重量	Machine	机器	1800 KG	
	Packing	包装	2100 KG	

Specifications are subject to change without notice. 以上参数可能随机器版本改变，请以厂家最新数据为准。