



COMPACT

DTF GARMENT PRINTING SOLUTION

—
Epson i3200/ i1600/ F1080

- Two Epson Heads
- CMYK + W
- Printing + Powder Treating
- 40cm/80cm Golden Size




• Features



Compact Integrated Design

Compact and elegant design, strong, space saving, easy operation, provide high accuracy output. Not only one partner for your printing business, but also a decoration for the company.



Golden Production Size

40cm/80cm working width and well matched PET film, and achieve golden production size for garments printing.



Integrated Control Centre

Convenient and high-efficiency.



Anti-collision System

Printer will automatically stop when the printhead carriage hits any unexpected object during working, and the system memory function supports continuing printing from the interruption part, reducing the material waste.



Multifunctional Machine for Mass Production

Apply to different fabric include cotton, polyester, nylon, denim, etc. Make the mass production of DIY t-shirts, hoodies, sportswear, pants, canvas bag to be convient.



• Specification

| Model No. | | DTF-800S | DTF-800D | DTF-400D | DTF-400E |
|----------------------------|--------|--|-----------------------|-----------------------|-----------------------|
| Printhead | | 2 × Epson i3200 | 2 × Epson i1600 | 2 × Epson i1600 | 2 × Epson F1080 |
| Resolution | | 2400dpi | 2400dpi | 2400dpi | 1440dpi |
| Ink Color | | CMYK + White | | | |
| Media | Size | 80cm | 80cm | 40cm | 40cm |
| | Types | PET Film | | | |
| Speed | 4 Pass | 12 m ² /h | 12 m ² /h | 9 m ² /h | 4.5 m ² /h |
| | 6 Pass | 7.5 m ² /h | 7.5 m ² /h | 5.5 m ² /h | 2.7 m ² /h |
| | 8 Pass | 5 m ² /h | 5 m ² /h | 3.5 m ² /h | 1.8 m ² /h |
| Ink Type | | Pigment Ink | | | |
| Application | | DIY Printing On T-shirt, Hoodies, Cap, Bag, Etc. | | | |
| Ink Droplet | | 1.5-21pl Variable | | | |
| Powder Shaking And Heating | | Standard Equipped | | | |
| Cleaning | | Automatic Cleaning, Anti-Clogging Flash Function & Capping System | | | |
| Feed & Take Up | | Automatic Media Feeding (Standard) & Take Up System (Standard) | | | |
| Environment | | Temperature: 20-28°C, Humidity: 40%-60% | | | |
| Rip Software | | Maintop (Standard) / FlexiPRINT (Optional) | | | |
| Interface | | USB 3.0 | | | |
| Power | | Machine 50/60HZ, 110/220V | | | |

Specifications are subject to change without notice. 以上参数可能随机器版本改变, 请以厂家最新数据为准。