

# Epson Series Eco Solvent Printer

1.6m Epson i1600 / i3200 Printhead

1.6米 爱普生 i1600 / i3200 户内外写真机

Variable Dot

可变墨滴

4 Color

4色写真

Single Head

单喷头






## ● Features 特点



### Epson PrecisionCore Printheads

Equipped with Epson i1600/i3200 print-head, powered by Epson PrecisionCore technology. Born for fast speed and long-term running.




### Heating and Drying System

Front and rear heating system, and front drying fan are standard equipped to help dry the printed material fast.




### Integrated Take Up System

It offers adjustable roll widths, making it suitable for various sized media rolls and applications



### Variable Dot Print Technology

Permitting the printer to provide smooth gradations, exceptional solid colors and optimum image quality in all print modes



### Free ICC Profiles

The SinoColor support provides a batch of free icc profiles for different major media and inks

★ New look has heavier, larger structure, and wider printing platform

★ Dual feeding bar for loading heavy media

★ Optional infrared heater for drying prints quickly



## ● Specification 参数

Model No.		型号	SJ-640D	SJ-640S
Printhead		喷头	1 × Epson i1600	1 × Epson i3200
Resolution		精度	2400dpi max	
Ink Color		色彩	CMYK	
Media 耗材	Size	尺寸	1.6 meter	
	Types	种类	Flex Banner , Vinyl, One Way Vision, Banner Cloth, Window Film, Mesh Etc. 灯箱布, 车贴, 单透贴, 条幅布, 玻璃贴膜, 网格布等	
Speed 速度	Draft	标准	21 m <sup>2</sup> /h	23 m <sup>2</sup> /h
	Production	精细	14 m <sup>2</sup> /h	16 m <sup>2</sup> /h
	Quality	照片	11 m <sup>2</sup> /h	12 m <sup>2</sup> /h
Ink Type		墨水	Eco Solvent Ink	
Ink Droplet		墨滴	1.5-21pl variable	
Cleaning		清洗	Automatic Cleaning, Anti-Clogging Flash Function & Capping System 自动清洗、闪喷、封喷头	
Feed & take up		收放布	Automatic Media Feeding (Standard) & Take up System (Optional)	
Environment		环境	Temperature: 20-28°C, Humidity: 40%-60%	
Rip Software		软件	Maintop (Standard)/ FlexiPRINT (Optional)	
Interface		接口	USB 3.0	
Power		电源	Machine 50/60HZ, 110 / 220V	
Size & Weight	Machine	机器	L2470×W650×H1100 mm / 150KG	
	Packing	包装	L2600×W850×H650 mm / 220KG	

Specifications are subject to change without notice. 以上参数可能随机器版本改变, 请以厂家最新数据为准。