

UV Roll To Roll Printer

3/4 Printheads | Variable Dot
4/5/6 Colors | White & Varnish

INDUSTRIAL GRADE

SINOCOLOR




● Features 特点



Different Printheads Available

Epson i3200-U, Ricoh GEN5, Ricoh GEN6 printheads available. Meet the demands of different clients.

爱普生i3200-U, 理光GEN5和GEN6喷头可选。满足不同客户需求。



Material Tension System

Tension media feeding system is standard equipped to guarantee the high accuracy of material stepping.

张力放布系统。保障高精度步进。



Negative Pressure System

Two advanced separate negative pressure systems. Simply and effectively ensure the continuous ink flow, and easy maintenance for multi-heads equipment.


配置高级的负压系统。稳定供墨，简化多头设备维护。



Dual guide rail

Dual guide rail configuration, guarantee the stability of long time running.

双导轨设计，提高设备长时间运行的稳定性



Anti-collision System

Printer will automatically stop when the carriage hit any unexpected object during working, and support continuing printing from the interruption part, reduce the material waste.

小车遇撞击自动停止，并支持中断处续打，减少意外带来的材料浪费

- ★ Well-designed tension type material feeding and take-up system. Ensure the high accuracy of material stepping.

精心设计的张力收放布系统，精确走步

- ★ Mature time-set stirring system for white ink, effectively decrease the problems caused by white ink precipitation.

成熟的白墨定时搅拌装置，有效防止UV白墨沉淀

- ★ Elegant and sleek appearance design, not only an advanced printing equipment, but also a decoration for the company.

简约大气的外观设计



● Specification 参数

| Model No. | 型号 | UR-2000S | UR-3200S | UR-3200R | UR-3200Rs |
|-------------------|-----------------|---|----------------------|----------------------|------------------------|
| Printing Head | 打印喷头 | 3/4 × Epson i3200-U | 3/4 × Epson i3200-U | 3/4 × Ricoh GEN5 | 3/4 × Ricoh GEN6 |
| Resolution | 打印精度 | 2400 dpi MAX | 2400 dpi MAX | 1200 dpi MAX | 1200 dpi MAX |
| Media 耗材 | Width 耗材宽度 | 1850 mm MAX | 3200 mm MAX | 3200 mm MAX | 3200 mm MAX |
| | Type 耗材种类 | Canvas, Leather, PET Film, Reflective Film, Soft Ceiling Film & More Flexible Material Etc. 天花软膜、灯布、车贴、皮革、PET膜、反光膜以及其他众多卷材 | | | |
| Ink 墨水 | Type 墨水类型 | UV Ink | | | |
| | Color 墨水颜色 | CMYK / CMYK+W / CMYK+W+V | | | |
| Speed 速度 | Curing 墨水固化 | High Quality Whater Cooling UV-LED Lamp 水冷UV-LED灯 | | | |
| | Color Mode 颜色模式 | CMYK | | | |
| | Draft 草图模式 | 56 m ² /h | 72 m ² /h | 30 m ² /h | 36 m ² /h |
| Production 标准模式 | Production 标准模式 | 28 m ² /h | 36 m ² /h | 21 m ² /h | 25.5 m ² /h |
| | Quality 精细模式 | 16 m ² /h | 20 m ² /h | 17 m ² /h | 20.5 m ² /h |
| Ink Supply System | 供墨系统 | Two advanced separate negative pressure systems (One for color and varnish, One for white). | | | |
| Cleaning | 清洗系统 | Automatic Cleaning, Anti-Clogging Flash Function & Capping System 自动清洗、闪喷、封喷头 | | | |
| Feed & TakeUp | 收放布 | Automatic Media Feeding (Standard) & Take up System (Optional) 自动收放布 | | | |
| Rip Software | 操作软件 | Photoprint | | | |
| Connector | 连接方式 | USB 3.0 | | | |
| Power | 电力消耗 | AC 110V / 220V ± 5%, 16A, 50/60Hz ± 1, 1500W MAX | | | |
| Size 尺寸 | Machine 机器尺寸 | L5170 x W920 x H1710 mm | | | |
| | Packing 包装尺寸 | L5270 x W1020 x H1940 mm | | | |
| Weight 重量 | Machine 机器重量 | 1000 KG | | | |
| | Packing 机器重量 | 1300 KG | | | |

Specifications are subject to change without notice. 以上参数可能随机器版本改变，请以厂家最新数据为准。