



A3 DTG T-shirt Printer

Digital Direct to Garment

T恤打印机

High Speed
速度快

Super Reliable
超稳定

White Circulation
白墨循环


Easy to Use
易于使用



DTG Printer

TP-300

● Features 特点



White ink double circulation system
With a built-in white ink double circulation system, effectively protects the printhead and avoids the clogging

白色墨水双循环系统
内置白色墨水双循环装置，有效保护喷嘴，避免堵塞




Converted from Original Epson
Better than a simple conversion. It is built with a lot customized parts to maximum the reliability.

改装原装爱普生打印机
秉承爱普生的高精度和高速度，稳定性升级



Ink Configuration
8 color : C+M+Y+K+WWWW

墨水配置方案
8色: C+M+Y+K+WWWW



High Strength Structure
1.2 mm cold-roll steel sheets, reinforced machines frame, more stable and durable

高强度的身体
1.2毫米冷轧钢板，增强机器意向性，更稳定耐用



Customized Motion System
Effectively improved the stability of the motion system. Much better than Epson original one which are made for home users.

升级运动系统
有效提升EPSON原装系统的稳定性和耐用性



● Specification 参数

Model No.	型号	TP-300
Printhead	打印喷头	Single Epson DX7
Resolution	打印精度	5760 x 1440 dpi Max
Max Speed	打印速度	50 sec for full size
Print Head Height	喷头高度	8.5 cm Max
Printing Size	打印尺寸	30 x 40 cm Max
Print Direction	打印方向	Intelligence double sided
Print Method	打印方法	Eight color on-demand inkjet (micro piezo print technology, intelligence drops transformation technology)
Height Adjust	高度调节	Electric
Distance of Print Head Printing		1-3 mm (1 mm is the best)
Ink Color	墨水颜色	8 Color (CMYK + 4W)
Ink Supply System	供墨系统	CISS
Ink Consumption	墨水消耗	15-20 ml /sqre meter
Ink Cartridge Type	墨盒类型	Split type
Min Ink Drop Size	墨滴大小	< 1.5 PL
Interface	输入接口	USB2.0
Rip Software	图像处理	Korean AcroRIP Software
Working Environment	工作环境	Temperature 18-30 Celsius, Humidity 30-70 RH, Clean room, Low dust, Less sun light
Power	电源输入	AC 110/220 V, 50 Hz/60 Hz
Size & Weight	Machine 机器	L770mm W640mm H460mm / 58KG
	Packing 包装	L890mm W750mm H550mm / 65KG

Specifications are subject to change without notice. 以上参数可能随机器版本改变，请以厂家最新数据为准。